Product Environmental Profile





Delphys BC 300

Uninterruptible power supply up to 300 kVA





Socomec is member of :





Member of WEEE Europe







The commitments of Socomec to respect the environment

As part of its environmental policy, Socomec is committed to:

- Incorporate the principles of the circular economy into the design of new products and services
- Promote longer product lifetimes
- Promote the use of environmentally responsible materials
- Design and develop solutions to further improve the energy efficiency of our products and services
- Inform our customers in a transparent manner about the environmental impact of our products throughout their life cycle.

To this end, Socomec is committed to constantly monitoring, anticipating and complying with environmental regulations as well as customer expectations relating to its products, and to ensuring that all those involved adhere to and take responsibility for its commitments.

PEP ecopassport® Registration number: SOCO-00068-V01.01-EN

Contact: http://www.socomec.com/contact-us_en.html





• Product information :

Reference product	
Model	Delphys BC 300
Sales reference	1630300023
Description	Uninterruptible power supply up to 300 kVA
General data	
UPS Configuration	Single
UPS topology	Double conversion
UPS Performance classification	VFI-SS-111
Number of phases available	Three phase
Power [W]	270000
Apparent power [VA]	300000
Acoustic noise [dB]	< 71 dBA
Efficiency	
Weighted UPS efficiency [%]	94,43%
Weight & dimensions	
Dimensions W*H*D [mm]	1000*1925*950
Mass without packaging [kg]	829,2
Mass of the packaging [kg]	77

The UPS is not equipped with an energy storage system.

Functional unit:

To ensure the supply of power to remain within specified characteristics to equipment with load of 100 watts for a RSL of 1 years.

Declared unit:

To ensure the supply of power to remain within specified characteristics to equipment with load of 270000 watts for a RSL of 15 years.

Mathematic relation between DU (declared unit) and FU (functional unit) mentionned in PSR-0010-ed2.0-EN 2023 12 08

References covered by this PEP with extrapolation rules:

- Delphys BC 300 with sales references: 1630300023; 1630300024; 1630300033
- Delphys BC 200 with sales references: 1630200023; 1630200024; 1630200033

Characteristics of the covered references:

Model	Power [W]	Power [W] Weighted UPS efficiency [%]		Packaging mass [kg]
Declared Unit: Delphys BC 300	270000	94,43%	829	77
Extrapolated unit: Delphys BC 200	180000	94,40%	500	72



Materials and substances

Declaration of the constitutives materials

Total mass of the Delphys BC 300 (including packaging): 906,2 kg among which packaging: 77 kg

For the reference product:

Plastics as % of w	Plastics as % of weight		ight	Other as % of weight		
Polyester	1,87%	Stainless steel	51,82%	Wood	5,58%	
Polyamide	1,63%	Aluminium and its alloys	14,82%	Electronic components	3,83%	
Epoxy resin	1,62%	Steel	8,60%	Cardboard	3,04%	
PVC	0,32%	Copper and its alloys	4,61%	Other inorganics	0,31%	
PE	0,30%	Other ferrous alloys	0,24%	Miscellanous	0,25%	
ABS	0,18%	Nickel and its alloys	<0,1%	Paper	<0,1%	
PBT	<0,1%	Zinc and its alloys	<0,1%	Other organics	<0,1%	
PC	0,33%	Precious metals	<0,1%			
Phenolic resin	<0,1%	Tin and its alloys	<0,1%			
PTFE	<0,1%	Lead and its alloys	<0,1%			
		Other metals	<0,1%			
Other plastics	0,31%					
Total Plastics: 60,34 kg	6,66%	Total Metals: 727,14 kg	80,24%	Total Others: 118,71 kg	13,10%	

Substances management

Socomec is leading a program to limit the use of hazardous substances in the design of new products and to monitor the presence of substances of concern in its supplies to anticipate future use restrictions.



Directive 2011/65/EU: Product references covered by this PEP meet the requirements of the RoHS Directive on the restriction of substances such as lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyl (PBB), polybrominated diphenyl ethers (PBDEs) and phthalates (DIBP, DEHP, BBP, DBP).



REACH 1907/2006 regulation: To the best of our knowledge, based on the supplier declarations, at the publication date of this document, the product do not contain any SVHC in a concentration above 0,1% per weight.

Manufacturing



The products covered by this PEP are manufactured on the production site of Huttenheim, France whose environmental management system has been ISO 14001 certified. Impacts on the environment are reduced by optimizing its energy consumption and by practicing a rigorous waste management.

Distribution

As part of its distribution policy aiming to respect the environment, Socomec is in favor of groupage transports and ISO 14001 certified logistic partners.

No reconditionning is planned for the product. This phase is consequently neglected.

The sizing of the packaging has been optimized to ensure the best possible protection of the product at the lowest possible volume in order to reduce the impact of the transport stage on the environment.



Installation

The installation phase consists in connecting the product to the existing electrical installation.

The installation does not generate any significant impacts on the environment, except impacts from packaging waste.

Use phase

Consumption scenario

Use phase scenario: European energy mix

Load (%)	25%	50%	75%	100%
Proportion of time spent (%)	25%	50%	25%	0%

Total energy consumption during 15 years

Total average energy consumption	946819 kWh
Average UPS efficiency	94,43%

Care and maintenance

It is recommended to carry out periodic specialized maintenance in order to keep the equipment at the maximum level of efficiency and to avoid the installation being out of service with possible damage/risks.

Typical parts which are subjects to maintenance:

Components	DC capacitor filtering	AC capacitor filtering	Fans	Power supply PCB
Number of replacement	2	1	3	1


Consumables

The product does not require consumables.

End of life

End of life treatment

The following parts require specific care and selective treatment in accordance with Annex VII of the WEEE Directive 2012/19/EU: Waste of electrical and electronic equipment. Maintenance and disassembly should always be conducted by qualified personnel.





Type of component	Item	Part mass	Location
LCD	UNIP7-U4	0,750 kg	1
Condensateur	E134238	3x 1,0 kg	2
Electronic cards	*	2,643 kg	3

^{*:} E962697T, E962837, E961137, E961147, E961337, S07002X01, S07078X01, E963367, S07002X02, UNIP7-DGP, E962727, E961217, E962747, S07013X02, E962637, E961297, E963426, E961857T, E962617, E962597, E962737, E964286

Recyclability potential of the product according to IEC TR 62635

The recyclability potential of the product is 80,63%.

This covers material and energy recovery potentials.

Additional information



This environmental declaration lists the information required in Annex A and B of IEC 62040-4 (Edition 1.0 2013-04) and EN 62040-4:2013 (2014-03).

Environmental impacts

Calculation methodology: life cycle assessment (LCA)



The calculation of the impacts on the environment was made using a life cycle assessment methodology in accordance with the ISO 14040 requirements and with PEP eco passport product category rules. For more details follow the link:

www.pep-ecopassport.org

This study was carried out with the following version of the software EIME and of the database:

EIME version: 5.9.4

Database version: CODDE-2022-01

For biogenic carbon storage the following methodology was used: 0/0

The whole life cycle has been taken into account:

Step	Geographical representativeness	Scenario
Manufacturing (M) (A1-A3)	Production of electronic components : Asia Production of other components and packaging : Europe Assembly : France	From the raw material extraction to the last Socomec logistic platform, including packaging Waste generated during manufacturing phase are taken into account.
Distribution (D) (A4)	Distribution scenario : Europe	From the last Socomec logistic platform to the final customer. No product reconditionning.
Installation (I) (A5)	Transport and treatment of packaging wastes : Local	Local road transport of 1000 km of generated wastes to the treatment site, end of life treatment.
Use phase (U) (B1-B7)	Energy mix : Europe Production of maintenance components: analog to manufacturing phase	Power consumption required during 15 years according to consumption scenario above mentionned.
End of life (EOL) (C1-C4)	Transport and treatment : Local	Road transport of 1000 km from the final customer to the treatment sites. End of life treatment.



Environmental impacts of the Delphys BC 300 per functional unit (power of 100W and a lifespan of 1 year)

The following impacts have been calculated to best represent geographically, temporally and technologically each step of the life cycle.

Indicators	Unit	Total impact	M (A1-A3)	D (A4)	I (A5)	U (B1-B7)	EOL (C1-C4)
Acidification	mol H+ eq.	5,63E-02	1,37E-03	7,50E-05	6,13E-06	5,49E-02	2,31E-05
Climate change - Total	kg CO2 eq.	9,81E+00	1,76E-01	1,18E-02	2,28E-03	9,61E+00	4,02E-03
Climate change - Biogenic	kg CO2 eq.	1,55E-02	3,10E-03	0*	0*	1,31E-02	0*
Climate change - Fossil	kg CO2 eq.	9,79E+00	1,73E-01	1,18E-02	3,01E-03	9,60E+00	4,02E-03
Climate change - Land use and land use transformation	kg CO2 eq.	2,36E-09	1,28E-09	0*	0*	1,08E-09	0*
Ecotoxicity, freshwater	CTUe	1,12E+02	8,26E+00	0*	0*	1,04E+02	1,57E-02
Particulate matter	disease occurrence	4,36E-07	9,30E-09	6,10E-10	0*	4,26E-07	1,80E-10
Eutrophication, freshwater	kg P eq.	2,76E-05	7,44E-07	4,44E-09	1,40E-08	2,65E-05	3,48E-07
Eutrophication, marine	kg N eq.	6,48E-03	1,95E-04	3,51E-05	2,27E-06	6,24E-03	1,02E-05
Eutrophication, terrestrial	mol N eq.	9,64E-02	2,20E-03	3,85E-04	1,84E-05	9,37E-02	1,10E-04
Human toxicity, cancer	CTUh	1,06E-06	1,05E-06	0*	3,54E-10	9,46E-09	0*
Human toxicity, non-cancer	CTUh	5,21E-08	6,75E-09	2,25E-11	7,92E-12	4,53E-08	1,01E-11
lonising radiation, human health	kBq U235 eq.	3,02E+01	1,58E+01	0*	0*	1,44E+01	0*
Land use	No dimension	1,93E-01	1,18E-03	0*	0*	1,91E-01	0*
Ozone depletion	kg CFC-11 éq.	6,21E-08	1,40E-08	1,81E-11	6,84E-11	4,80E-08	3,03E-11
Photochemical ozone formation, human health	kg NMVOC eq.	2,08E-02	6,65E-04	9,72E-05	5,24E-06	2,00E-02	2,81E-05
Abiotic resource depletion - fossil fuels or resource depletion - fossils	MJ	2,52E+02	7,31E+00	1,65E-01	0*	2,45E+02	5,61E-02
Abiotic resource depletion - elements or resource depletion - metals and minerals	kg Sb eq.	2,12E-05	1,62E-05	0*	0*	5,03E-06	0*
Water use	m³ eq.	-7,60E-01	-1,12E+00	0*	0*	0*	0*
Net use of freshwater	m³	-1,77E-02	-2,61E-02	0*	0*	0*	0*
Total Primary Energy	MJ	2,99E+02	7,42E+00	1,65E-01	0*	2,92E+02	5,66E-02
Total use of non-renewable primary energy resources	MJ	2,52E+02	7,31E+00	1,65E-01	0*	2,45E+02	5,61E-02
Total use of renewable primary energy resources	MJ	4,70E+01	1,09E-01	0*	6,53E-03	4,69E+01	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	2,52E+02	7,23E+00	1,65E-01	0*	2,45E+02	5,61E-02
Use of non renewable primary energy resources used as raw material	MJ	1,00E-01	7,88E-02	0*	0*	2,16E-02	0*
Use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	4,70E+01	5,74E-02	0*	6,53E-03	4,69E+01	0*
Use of renewable primary energy resources used as raw material	MJ	5,28E-02	5,19E-02	0*	0*	8,79E-04	0*
Use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of secondary material	kg	2,16E-03	2,05E-03	0*	0*	1,09E-04	0*
Hazardous waste disposed	kg	5,81E-01	2,98E-01	0*	0*	2,83E-01	0*
Non hazardous waste disposed	kg	1,56E+00	1,30E-01	4,16E-04	4,28E-03	1,40E+00	2,12E-02
Radioactive waste disposed	kg	4,98E-04	1,33E-04	2,96E-07	4,70E-07	3,64E-04	4,95E-07
Components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*
Exported Energy	MJ	1,19E-03	4,61E-04	0*	7,27E-04	0*	0*



Materials for energy recovery	kg	0,00E+00	0*	0*	0*	0*	0*
Materials for recycling	kg	9,50E-04	3,20E-06	0*	9,44E-04	3,13E-06	0*

Biogenic carbon content in the reference product:

Biogenic carbon content of the product	kg of C	0,00E+00	0*	N/A	N/A	N/A	N/A
Biogenic carbon content of the associated packaging	kg of C	2,73E+01	2,73E+01	N/A	N/A	N/A	N/A

NB: 0* means that this impact either represents less than 0.01% of the total life cycle of the reference flow, or has no impact (in the case where the total impact is zero).

The aforementionned impacts (except for the biogenic carbon content) are declared for the functional unit of the reference product.

The environmental impacts of the reference product per declared unit can be calculated by multiplying the values of the environmental indicators by the factor available in the following table.

Life cycle phase	All life cycle phase
Factor	40500

Other covered references

For the products covered by the PEP other than the reference product, the environmental impacts of each phase of the lifecycle are calculated by multiplying the declared unit impacts values with the following extrapolation factors:

Model	M (A1-A3)	D (A4)	I (A5)	U (B1-B7)	EOL (C1-C4)
Delphys BC 300	1,00	1,00	1,00	1,00	1,00
Delphys BC 200	0,63	0,63	0,94	0,67	0,60

Registration number : SOCO-00068-V01.01-EN		Drafting Rules: "PEP-PCR-ed4-EN 2021 09 06"				
			Supplemented by: "PSR-0010-ed2.0-EN 20	23 12 08"		
Verifier accreditation number : VH12 Information			nformation and reference documents : www.pep-ecopassport.org			
Date of issue:		01-2024	Validity period : 5 years			
Independant verification of the declaration and data, in compliance with ISO 14025 : 2006						
Internal:	External:					
The PCR review was	PEP					
PEPs are compliant	eco					
The components of	PASS					
Document complies	PORT _®					
declarations"						

This document is intended to be only informative and non-contractual and does not create any right or obligation or commitment for Socomec towards its associates, customers or any other person or entity. All the values indicated in this document may change depending on many factors (use conditions, applications, installations, environment...). The life time mentioned in this document is only indicative and is not intended to be the minimal, maximal or average life time of the product.