

Selection guide

Enclosed transfer switches

Which
Application?Which power
supply?

	MTSE (manual)				
	25 to 100 A	160 to 630 A	32 to 100 A	160 to 1600 A	
					
	COMO CS	SIRCOVER	SIRCO M	SIRCOVER	
Type of enclosure					
Polycarbonate	•	•			
Steel			•	•	
Number of poles					
2 poles					
3 poles					
4 poles	•	•	•	•	
Supply type					
12 VDC power supply					
Single 230 VAC supply					
Double 230 VAC supply					
Mimic panel					
LED					
D10					
D20					
Application					
Network-Network	•	•	•	•	
Network-Genset	•	•	•	•	
Genset-Genset	•	•	•	•	
Configuration					
Configuration by potentiometers and dip switches					
Configuration by screen and keyboard					
Auto-configuration of voltage and frequency					
IP					
3x					
41					
54		•			
65	•	•	•	•	
Connection					
High-Low	•	•	•	•	
Low-High					
Low-Low	•	•	•	•	

(1) Optional.

(2) 40 to 160 A only.

Functionalities?

Environment?

RTSE (remotely operated)			ATSE (automatic)					
40 to 160 A		200 to 3200 A	40 to 160 A			200 to 3200 A		40 to 3200 A
								
ATyS d M	ATyS d M	ATyS r	ATyS g M		ATyS p M	ATyS g	ATyS p	ATyS Bypass
•			•	•				
	•	•			•	•	•	•
•			•					
	•	•		•	•	•	•	•
		•						
•	•		•	•	•	•	•	•
		•				•		•
					•		•	•
•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
•	•	•						
			•	•	•	•		
					•		•	•
			•	•	•	•	•	•
	•				•	•		
		•		•				•
•	•	•	•		•	•	•	•
•	•		•		•	•		
•	•	•	•	•	•	•	•	•